



SPECIFICATION SHEET
 KL



LIGHT WEIGHT RANGE | KL
 SWL 300 Kg



The Light Weight mobile step is based on the Industrial Range, however it is manufactured with 19mm light weight tube. Perfect for use in stores, warehouses, archives, retail and office environments.

- **Platform height** between 500 - 1500 mm
- **Tread size** 550 (W) x 200 (D) mm
- **Platform Size** 550 (W) x 400 (D) mm

This range comes fully welded and ready to use!

LIGHT WEIGHT RANGE

Dimensions

| Product Code | Treads | Working Platform Height | Working Height | Overall Height | Overall Width | Overall Length | Weight | Brake Type |
|--------------|--------|-------------------------|----------------|----------------|---------------|----------------|--------|-----------------|
| KL 02 | 2 | 500 | 1500 - 2250 | 1500 | 650 | 605 | 20 | Plunger castors |
| KL 03 | 3 | 750 | 1750 - 2500 | 1750 | 650 | 758 | 28 | Plunger castors |
| KL 04 | 4 | 1000 | 2000 - 2750 | 2000 | 650 | 911 | 32 | Plunger castors |
| KL 05 | 5 | 1250 | 2250 - 3000 | 2250 | 850 | 1178 | 50 | Central brake |
| KL 06 | 6 | 1500 | 2500 - 3250 | 2500 | 850 | 1332 | 58 | Central brake |

Please Note : All dimensions are approximate and shown in mm, with weights shown in Kg.

Due to our ever-improving environment, we may make enhancements to our products which effect dimensions. Therefore reserve the right to amend these at any time to better serve our customer.

Unit 12 Murray Houses, Murray Road, Ottershaw, Surrey, KT16 0HW

Web: www.llmhandling.co.uk

Email: sales@llmhandling.co.uk